



TECHNICAL DATA		50 Hz	60 Hz
• Power (with ATEX certified vacuum unit)	kW - HP	4 - 5,5	4,6 - 6,3
• Input voltages ^{1) 2)} Current settings available	V A	690Y 4,5Y	---
		400D 7,8D	460D 7,6D
• Electrical cable length Electrical plug		9 meters Not supplied	
• ATEX mark		 II 3GD - Ex c IIB T3 (200°C) Gc - Ex c t IIIB T135°C Dc	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP 55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmH ₂ O	3.100 2.600	3.500 2.900
• Maximum air flow	l/min - m ³ /h	5.333 - 320	6.083 - 365
• Acoustic level ^{d)}	dB (A)	69	72
• Dust bin: capacity wheels diameter	l mm	90 60	
• Diameters: material inlet wheels ⁴⁾ (front - rear)	mm	70 200 - 150	
• Dimensions: L x W x H (H.008) Weight	mm kg	1.120 x 620 x 1.450 (1.770) 130	
• Packing size ⁵⁾ : L x W x H (H.008) Weight	mm kg	1.140 x 730 x 1.700 (2.100) 146	
• Primary filter		Star filter	
Surface area Diameter	cm ² - m ² mm	19.500 - 1,95 460	
Dust Class ^{6) e)} Media ⁷⁾		M Antistatic polyester	
Filter cleaning ⁸⁾		Ergonomic manual shaker	
• Automatic filter cleaning - Optional		Cartridges kit	
Surface area Nominal output	cm ² - m ² m ³ /h	56.400 - 5,64 2.030	
Dust Class ^{e)} Media		M Antistatic polyester	
Compressed air consumption pressure	nl/min bar	48 4 ÷ 6	
• Upstream absolute filter - Optional		HEPA 14	
Surface area Nominal output	cm ² - m ² m ³ /h	28.000 - 2,8 480	
Dust Class ^{f)} Media		H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		99,995%	

¹⁾ Other input voltages upon request

²⁾ Default factory setting: 400 V - 50 Hz

³⁾ Maximum vacuum in continuous run

⁴⁾ Antistatic wheels

⁵⁾ Standard packing size

⁶⁾ PTFE coated antistatic star filter available upon request

⁷⁾ Other materials available according to the material to be vacuumed

⁸⁾ Electric filter shaker with push-button available as optional

Normatives: a) IEC60529; b) IEC60085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• K3.Z2	90 litres three phase vacuum cleaner - IP55 - ATEX zones 2, 22
---------	--

OPTIONS

• 001	AISI 304 stainless steel dust bin (instead of the painted one)	included
• 002	AISI 304 stainless steel dust bin and filtering chamber	included
• 003	Entirely made out of AISI 304 stainless steel	upon request
• 004	Liquids switch off	not available
• 005	Upstream absolute filter (HEPA)	
• 006	Electric filter shaker with push-button	upon request
• 008	Automatic reverse jet cartridge filtering system	upon request
• 076	Dust bin overfilling switch off	upon request
•	Reinforced dust bin	upon request
•	On/off arrangement through micro-switch	upon request
•	Overheating safety relief valve	included

For an effective and proper use according to your application requirements, please see our accessories and spare parts catalogue.
Versions available: • L-M-H filtration (for hazardous powders vacuuming) certification

