



**CONDUCTIVE
AND
NO CONDUCTIVE DUST**

TECHNICAL DATA		50 Hz	60 Hz
• Power (with ATEX certified vacuum unit)	kW - HP	15 - 20,55	17,3 - 23,7
• Input voltages ^{1) 2)} Current settings available	V A	690Y 15,3Y 400D 26,5D	--- 460D 26,5D
• Electrical cable length Electrical plug		9 meters Not supplied	
• ATEX mark		 II 2D - Ex c t IIIC T125°C Db	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP 65 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmHg	5.200 3.900	5.400 4.000
• Maximum air flow	l/min - m³/h	7.833 - 470	10.166 - 610
• Acoustic level ^{d)}	dB (A)	74	78
• Dust bin: capacity wheels diameter	l mm	175 100	
• Diameters: material inlet wheels ⁴⁾ (front - rear)	mm	100 250 - 200	
• Dimensions: L x W x H (H.005 - H.008) Weight	mm kg	1.500 x 740 x 2.060 (2.100 - 2.170) 340	
• Packing size ⁵⁾ : L x W x H (H.005 - H.008) Weight	mm kg	1.500 x 800 x 2.250 (2.250 - 2.320) 360	
• Primary filter		Star filter	
Surface area Diameter	cm² - m² mm	35.000 - 3,5 560	
Dust Class ^{6) e)} Media ⁷⁾		M Antistatic polyester	
Filter cleaning ⁸⁾		Ergonomic manual shaker	
• Automatic filter cleaning - Optional		Cartridges kit	
Surface area Nominal output	cm² - m² m³/h	94.800 - 9,48 3.410	
Dust Class ^{e)} Media		M Antistatic polyester	
Compressed air consumption pressure	nl/min bar	48 4 ÷ 6	
• Upstream absolute filter - Optional		HEPA 14	
Surface area Nominal output	cm² - m² m³/h	120.000 - 12,0 1.200	
Dust Class ^{f)} Media		H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		99,995%	

¹⁾ Other input voltages upon request

²⁾ **Default factory setting: 400 V - 50 Hz**

³⁾ Maximum vacuum in continuous run

⁴⁾ Antistatic wheels

⁵⁾ Standard packing size

⁶⁾ PTFE coated antistatic star filter available upon request

⁷⁾ Other materials available according to the material to be vacuumed

⁸⁾ Electric filter shaker with push-button available as optional

Normatives: a) IEC60529; b) IEC60085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• **K11S.021** 175 litres three phase vacuum cleaner - IP65 - ATEX zone 21

OPTIONS

• 001	AISI 304 stainless steel dust bin (instead of the painted one)	included
• 002	AISI 304 stainless steel dust bin and filtering chamber	included
• 003	Entirely made out of AISI 304 stainless steel	upon request
• 004	Liquids switch off	not available
• 005	Upstream absolute filter (HEPA) - version: painted AISI 304 stainless steel	
• 006	Electric filter shaker with push-button	upon request
• 008	Automatic reverse jet cartridge filtering system	upon request
• 076	Dust bin overfilling switch off	upon request
•	Reinforced dust bin	upon request
•	On/off arrangement through micro-switch	upon request
•	Overheating safety relief valve	included

For an effective and proper use according to your application requirements, please see our accessories and spare parts catalogue.
Versions available: • **L-M-H** filtration (for hazardous powders vacuuming) certification

