

TECHNICAL DATA		50 Hz	60 Hz
• Power	kW - HP	4 - 5,5	not available
• Input voltages ^{1) 2)} Current settings available	V A	360Y ... 440Y 9,5Y	not available
		200D ... 240D 16,4D	not available
• Electrical cable length Electrical plug type		9 meters 4 poles (5 poles upon request)	
• ATEX mark		NO ATEX	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmH ₂ O	5.100 3.700	not available
• Maximum air flow	l/min - m ³ /h	5.334 - 320	not available
• Acoustic level ^{d)}	dB (A)	74	not available
• Tank capacity:	l	400	
• Diameters: material inlet wheels ⁴⁾ (front - rear)	mm	50 200 - 200	
• Dimensions: L x W x H Weight	mm kg	1.407 x 660 x 1.927 221	
• Packing size ⁵⁾ : L x W x H Weight	mm kg	1.500 x 800 x 1.900 236	
• Expelling system (supplied with hose and gun)			
Pump power	kW - HP	0,78 - 1	
Pump capacity	l/min	220	
Hose length		3 meters	
• Swarf basket			
Capacity	l	60	
Diameter	mm	460	
Diameter swarf basket holes	mm	2	

1) ...

2) **Default factory setting: 400 V - 50 Hz**

3) Maximum vacuum in continuous run

4) Marks proof wheels with bearings

5) Standard packing size

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

AVAILABLE VERSIONS

• KOIL440T	400 litres three phase vacuum cleaner	

OPTIONS

• 209175	Nylon filter 300 micron - Ø360	not suitable
• 209180	Nylon filter 200 micron - Ø360	not suitable
• 209174	Nylon filter 300 micron - Ø460	
• 209181	Nylon filter 200 micron - Ø460	



For an effective and proper use according to your application requirements, please see our AP catalogue.

Versions available: • **L-M-H** filtration (for hazardous powders vacuuming) certification